

Product data sheet Characteristics

LE1M35U722

TeSys; TeSys LE, enclosed DOL starter, 12...16 A, 240 V AC coil





Main Range TeSys Product name TeSys LE Device short name LE1M Product or component **Enclosed DOL starter** type Device application Standard AC-3 Utilisation category Device composition Contactor Earth terminal Neutral terminal Thermal overload relay Thermal protection 12...16 A adjustment range Motor power kW 4 KW at 240 V AC 50/60 Hz 7.5 KW at 415 V AC 50/60 Hz 7.5 KW at 380/400 V AC 50/60 Hz 3.7 kW at 220/230 V AC 50/60 Hz

240 V AC 50/60 Hz

Push-button start green I Push-button stop/reset red O

Complementary

2 ISO20 top	
2 ISO25 top	
2 Pg 13 top	
2 Pg 21 top	
2 ISO20 bottom	
2 ISO25 bottom	
2 Pg 13 bottom	
2 Pg 21 bottom	
2 Pg 16 bottom	
78 mm	
160 mm	
108 mm	
0.6 kg	
	2 Pg 13 top 2 Pg 21 top 2 ISO20 bottom 2 ISO25 bottom 2 Pg 13 bottom 2 Pg 13 bottom 2 Pg 21 bottom 2 Pg 16 top 2 Pg 16 top 78 mm 160 mm

[Uc] control circuit

voltage Control type

Environment

Material	ABS (acrylonitrile butadiene-styrene)	
IP degree of protection	IP65 conforming to IEC 60529	
Standards	IEC 60947-4-1	
Ambient air temperature for operation	-540 °C	
Environmental characteristic	Standard environment	
Product certifications	UKCA	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.5 cm
Package 1 Width	16.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	591.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	6
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.001 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	☑ End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty 18 months	

Life Is On | IICLIPSAL