

# 100SB11

Allen-Bradley 100C Auxiliary Contact with 1NO Contact and 1NC Contact Side Mount



**Allen-Bradley**

by ROCKWELL AUTOMATION

CONTACTORS



<b>Component type</b>	Auxiliary contact block
<b>Range</b>	100C
<b>Model</b>	N/A
<b>Product status</b>	Existing

The Allen-Bradley 100-C contactor line offers compact, high-performance design in 9 to 97 A contactors. These energy efficient contactors are designed to control motors and other loads. Straightforward wiring and installation process ensure quick and easy setup, reducing downtime and increasing productivity.

## ELECTRICAL

Number of contacts as normally open contact	1.0
Number of contacts as normally closed contact	1.0
Rated insulation voltage $U_i$	690.0 V
Rated operation current $I_e$ at AC-15, 24 V	6.0 A
Rated operation current $I_e$ at AC-15, 120 V	6.0 A
Rated operation current $I_e$ at AC-15, 240 V	5.0 A
Rated operation current $I_e$ at AC-15, 400 V	3.0 A
Rated operation current $I_e$ at DC-12, 24 V	6.0 A
Rated operation current $I_e$ at DC-12, 110 V	1.0 A
Rated operation current $I_e$ at DC-12, 220 V	0.5 A
Rated operation current $I_e$ at DC-13, 24 V	5.0 A
Rated operation current $I_e$ at DC-13, 110 V	0.68 A
Rated operation current $I_e$ at DC-13, 220 V	0.32 A
Contact rating current (Min)	10.0 mA
Contact rating voltage (Min)	17.0 V
Rated operation current $I_e$ at AC-15, 230 V	5.5 A

## CONSTRUCTION

Mounting method	Side mounting
-----------------	---------------