

# 1606XLSRED

Allen-Bradley 1606 Power Supply HP Redundancy Module 10 to 60V DC 20A



**Allen-Bradley**

by ROCKWELL AUTOMATION

POWER SUPPLIES



<b>Component type</b>	DC-power supply
<b>Range</b>	1606
<b>Model</b>	N/A
<b>Product status</b>	Existing

The Allen-Bradley 1606 Switched Mode Power Supplies are the ideal solution for reliable and efficient power supply. Features compact design with wide input voltage range (single and multi phase AC and DC), power boosts, in-built redundancy and conformal coating for harsh environments. Available with multiple output voltage levels and wide power output range to accommodate various load sizes.

## ELECTRICAL

<b>Voltage type of supply voltage</b>	DC
<b>Frequency</b>	50 - 60 Hz
<b>Nominal current (In)</b>	8.0 A
<b>1st secondary output voltage</b>	10 - 60 V
<b>Max. output current 1</b>	20.0 A
<b>Nominal value output current 1</b>	20.0 A
<b>Nominal value output voltage 1</b>	24.0 V
<b>Power output</b>	480.0 W
<b>Power consumption</b>	17.0 VA
<b>Type of electric connection</b>	Spring clamp connection
<b>With LED indication</b>	Yes

## CONSTRUCTION

<b>Rail mounting possible</b>	Yes
<b>Degree of protection (IP)</b>	IP20

## DIMENSIONS

<b>Width</b>	32.0 mm
<b>Height</b>	124.0 mm
<b>Depth</b>	102.0 mm
<b>Weight</b>	0.29 kg

## ENVIRONMENT

<b>Operating temperature</b>	-40 - 70 °C
------------------------------	-------------