

Horizon D Series

Residential metering enclosures for NT applications



- Designed for both single and multi-phase installations.
- Provide safety, quality and performance.
- Suitable for domestic and light commercial metering applications.
- Easy-to-use gravity catch
- Ratchet sliding cable entry
- RotaDIN rotating / removable DIN section.
- Cord retainer for easy retention of extension cords.
- Identification with covered labelling section.
- Weatherproof installation label for AS/NZS3000 compliance.
- Padlockable facility.
- External frame mounting brackets.
- Meter lock-off device.
- Manufactured from 1.0 galvanised steel to Z275.
- Powdercoated Light Grey RAL7035.



ORDERING GUIDE

Part Number	DIN space	Inclusions		Dimensions (mm)			Panel (mm)		
		RCCB Link [#]	MCB	Height	Width	Depth	Height	Width	Depth Behind
D10*	18-pole	•	63A	600	400	300	390	385	75
D20	24-pole	•		688	485	278	480	461	75
NQ/DIN*	18-pole			600	600	270	575	560	75
Q41**				600	400	300	550	385	75
MD061802*	18-pole			600	400	270	590	385	75

* Sized for block construction work

[#] RCCB Links provide RCD expansion to 3 circuits

[†] While stocks last

ACCESSORIES

Part Number	Description	D10	D20	NQ/DIN	Q41	MD061802
HZN/FK8	Flush kit for flush mounting		•			