

High Temperature

Silicone Rubber Cables 150°C - 200°C



Application:

Industrial heating and cooling, areas where extreme high and low temperatures are apparent

Benefits	
Wide Temperature Range	Silicone rubber insulation is suitable in extreme high and low temperatures
Flexible Stranding	Class 5 flexible conductor stranding
Acid and Oil Resistance	Good resistance to oils, gasoline and some acids
Marine Applications	Tinned copper conductor minimises corrosion in marine environments
Halogen Free	Silicone rubber insulation does not release corrosive gases when ignited
Features	
✓ R-S-200 insulation has a very wide operating range between -50°C and + 200°C	
✓ Tinned copper conductors provide excellent corrosion resistance at elevated temperatures	
✓ Silicone rubber exhibits excellent electrical resistance	
✓ Good flame retardance with zero halogens	
Construction	
Conductor	Tinned annealed copper wire, class 5
Insulation	R-S-200 (0.5mm ² - 6mm ² single core, R-S-150 other sizes)
Colours	Blue, black, brown, green, grey, orange, purple, pink, red, white, yellow, 3 Core – Blue, brown and green, black outer sheath
Ratings	
Temperature	R-S-200 -50°C to + 200°C R-S-150 -10°C to +150°C
Voltage	0.6/1kV
Applicable Standards	AS/NZS1125, AS/NZS3808, AS/NZS3191



Flexible Conductor:
Class 5



Tinned Copper
for Corrosion Resistance



Minimum Service
Temperature:
-50°C



Maximum Service
Temperature:
200°C Single Core up to
6mm² other sizes 150°C



Maximum Short Circuit
Temperature:
350°C (Max 5s)



Grease & Minerals Oils
Resistant



Chemical & Oil Resistant



UV Resistant



Low Temperature Resistant



Halogen Free



Minimum Recommended
Bend Radius Fixed 6 x OD

SYDNEY (Head Office)
102 Old Pittwater Road
Brookvale NSW 2100
Phone: 02 9938 5622
Fax: 02 9938 3973

BRISBANE
2/284 Musgrave Road
Coopers Plains QLD 4108
Phone: 07 3277 5811
Fax: 07 3274 0080

MELBOURNE
9/24-26 Carrick Drive
Tullamarine VIC 3043
Phone: 03 9335 2600
Fax: 03 9330 3903

NEWCASTLE
64 Orlando Road
Lambton NSW 2299
Phone: 02 4956 2044
Fax: 02 4956 1983

WESTERN AUSTRALIA
1 Karratha St
Welshpool WA 6106
Phone: 08 9351 9966
Fax: 08 9356 2522



Silicone Rubber Single Core - 200°C

Bambach Item Code	Conductor CSA mm ²	Conductor Stranding No. of Strands/mm	Nom Ø mm	Current Rating* Amps	Weight kg/km
10685A	0.5	16/0.20	2.7	19	12
13005	0.75	24/0.20	2.9	24	15
15105	1	32/0.20	3.3	28	19
17025	1.5	30/0.25	3.6	37	24
18765	2.5	50/0.25	4.0	50	35
20285	4	56/0.30	4.7	67	51
21640	6	84/0.30	6.1	87	72

Silicone Rubber Single Core - 150°C

Bambach Item Code	Conductor CSA mm ²	Conductor Stranding No. of Strands/mm	Nom Ø mm	Current Rating* Amps	Weight kg/km
22880A	10	140/0.30	8.2	120	115
23960A	16	224/0.30	9.4	165	176
24980A	25	350/0.30	11.0	215	264

Silicone Rubber Multi Core - 150°C

Bambach Item Code	Conductor CSA mm ²	Conductor Stranding No. of Strands/mm	Nom Ø mm	Current Rating [†] Amps	Weight kg/km
25720	2 x 0.75	24/0.20	7.0	24	70
25760	3 x 0.75	24/0.20	8.0	20	80
25980	3 x 1	32/0.20	9.0	24	110
26980	3 x 1.5	30/0.25	10.0	31	140
27015	3 x 2.5	50/0.25	12.0	43	180

*Current ratings based on AS/NZS3008.1.1:2009 table 17 column 2

†Current ratings based on AS/NZS3008.1.1:2009 table 17 column 4