



# Compression Terminal

By Burndy  
Catalog # [YAV06M4](#)

Non insulated Cu tubular terminals, Metric, 1 Hole/W/insp W,  
4-6 mm Class2, Tin - Electro Plated.



## Application

Metric Wire Termination

## General

Connector Type	METRIC
Die Index	11
Feature - Barrel Style	Chamfered
Feature - Barrel Type	Standard
Finish Type	Tin-Plated
Material	COPPER
Physical Attribute - Number of Holes	1
Plated	Y
Plating Type	Tin - Electro Plated
Trade Name	HYLUG™
Type	Metric Terminals
UPC	781810235232
UPC 12 Digit	7818102352322

## Dimensions

Dimension - B Length inch	0.41 in
Dimension - Bolt Size fraction	#8
Dimension - D inch	0.47 in
Dimension - Hole Size fraction	#8
Dimension - Hole Size inch	0.18
Dimension - Hole Size mm	4.6 mm
Dimension - L Length Overall mm	23.9 mm
Dimension - Length Overall inch	0.94 in
Dimension - N inch	0.19 in
Dimension - Outside Diameter inch	0.21 in
Dimension - Pad Width inch	0.38 in
Dimension - Strip Length inch	0.43 in
Dimension - Stud Size fraction	#8
Dimension - Stud Size inch	#4
Dimension - Z inch	0.26 in
Physical Attribute - Tongue Angle	Straight

## Electrical Ratings

Voltage - Maximum	35000
Voltage Rating	35 kV

## Conductor Related

Conductor - Copper Str Size	4-6 mm <sup>2</sup>
Conductor - Material	COPPER
Conductor Size	4-6 mm <sup>2</sup>
Conductor Type	CLASS 2

## Certifications and Compliance

Certification - CSA Approved	No
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Standards - RoHS Compliance Status	CM
UL Listed	No

## Logistics

Carton Quantity	100
Minimum Pack Quantity	100

## Product Assets

[3D Models - YAV06M4\\_MODEL-STEP](#)  
[3D Models - YAV06M4\\_MODEL-PDF](#)  
[3D Models - YAV06M4\\_MODEL-IGES](#)  
[Sales Drawings - 50025521](#)



A proud member of the Hubbell Family.

