

# **Compression Terminal**

By Burndy Catalog # YAV95M12

Non insulated Cu tubular terminals, Metric, 1 Hole/W/insp W, 95mmClass2, M12 stud, Tin - Electro Plated, 14 Index.



#### **Application**

Metric Wire Termination

#### General

Connector Type METRIC
Die Index 14

Feature - Barrel Style • Chamfered

Skived

Finish Type Tin-Plated Material COPPER

Physical Attribute - Number of 1

Holes

Plated

Plating Type Tin - Electro Plated

Trade Name HYLUG™

Type Metric Terminals
UPC 781810237540
UPC 12 Digit 7818102375400

#### **Dimensions**

Dimension - B Length inch 0.81 in Dimension - Bolt Hole Size 0.52 in

inch

Dimension - Bolt Size fraction 1/2
Dimension - Bolt Size inch 0.5
Dimension - Hole Size fraction 1/2
Dimension - Hole Size inch 0.53
Dimension - Hole Size mm 13.5 mm

Dimension - L Length Overall 59.9

mm

Dimension - Length Overall 2.36

inch

Dimension - N inch 0.47 in Dimension - Outside Diameter 0.63

inch

Dimension - Pad Width inch 0.93 in

Dimension - Strip Length inch

Dimension - Stud Size fraction

Dimension - Z inch

0.87 in

1/2

0.55 in

Straight

Physical Attribute - Tongue

Angle

**Electrical Ratings** 

Voltage - Maximum 35000 Voltage Rating 35 kV

**Conductor Related** 

Conductor - Copper Str Size 2/0

Conductor - Copper Str Size 95 mm<sup>2</sup>, 2/0 AWG

Range

Conductor - Material COPPER
Conductor Size 95 mm2
Conductor Type CLASS 2

#### **Certifications and Compliance**

Certification - CSA Approved No
Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Standards - RoHS Compliance CM

Status

UL Listed No

### Logistics

Carton Quantity 10 Minimum Pack Quantity 10

## **Product Assets**

3D Models - YAV95M12\_MODEL-PDF 3D Models - YAV95M12\_MODEL-STEP 3D Models - YAV95M12\_MODEL-IGES Catalogs - Full Line BURNDY Catalog

Sales Drawings - 50025521