



ARGO-1200

CLEVERTRONICS 240V ARGO LED WEATHERPROOF BATTEN WITH SWITCHABLE COLOUR & OUTPUT



PRODUCT INFORMATION

Part Number	ARGO-1200
MIC	AUB04620360001
Description	240V ARGO 1200mm Weatherproof Batten with Switchable Colour & Output
Construction	Polycarbonate Base, Polycarbonate Diffuser and Captive Stainless-Steel Clips (SS301)
Mounting	Surface mount
Dimensions L x W x H	1265mm x 121mm x 88mm
Weight	2.3 kg
Diffuser	Polycarbonate
Driver / Ballast	LED Driver – 40w Stallion, SP
Lamp(s)	Dual LED strip module, 3,000K warm white, 5,700K cool white, 50,000h life [L70/B50 Ta 40°C], Ra>80
Operating Voltage	240V AC; 50Hz
Power Factor	0.95
Supply Current	180mA +/- 20mA
Inrush Current (Max)	15.909A, 160µs
Earth Leakage	0.037-0.047mA
Total lumen output	4318lm (122lm/W @4000K, based on non-emergency), details see table below
Power Consumption	see table below
IP Rating	IP65
Operating Temperature	-25°C to 40°C
Impact Rating	IK08
Alternate Part Number	F4WB
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS60598.1
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1330083	LED Driver - 40w Stallion, SP

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.

Colour	Power Consumption Standby Lamp ON		Total Lumen Output	
	High Output (700mA)	Low Output (350mA)	High Output (700mA)	Low Output (350mA)
3000K	38 W	20 W	3819 lm	2260 lm
4000K	35 W	19 W	4318 lm	2431 lm
5700K	38 W	20 W	4100 lm	2400 lm