

CLEVERTRONICS LP LIFELIGHT PRO, BLACK



PRODUCT INFORMATION

| | |
|-----------------------|---|
| Part Number | CLIFE-PRO-BLK |
| MIC | AUT02310020003 |
| Description | LP Premium Lifelight PRO, High Performance, Recessed Emergency Light, Enabled with Clevertest Plus, Black |
| Construction | PC/ABS head |
| Mounting | Recessed mount |
| Dimensions L x W x H | 232mm x 40mm x 40mm (Control pack) 60mm head diameter (95mm with adaptor plate) |
| Ceiling Hole Cut-Out | 51mm, 85mm (with adaptor plate) |
| Minimum Ceiling Depth | 200mm, 120mm (with adaptor plate) |
| Weight | 0.8kg |
| Operating Mode | Non-maintained |
| Testing System | Clevertest Plus Enabled (Not activated by default) |
| Battery | Lithium Iron Phosphate, 3.2V 6400mAh |
| Charging Method | Intelligent current limited constant voltage |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V AC; 50Hz (supplied with a 2 core and earth flex and plug) |
| Power Consumption | 0.4 Watts (Standby), 2.7 Watts (Max) |
| IP Rating | IP20 |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C ₀ =D63 C ₉₀ =D63 |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|----------------|--|
| 1550230 | BATT:LP 3.2V 6400mAh.200mm lead.Brkt. |
| AUM02370100001 | Lifelight Pro, Control Only, LP, OWC |
| 1100841 | Lifelight Pro Head Assbly,Rnd,Large+Ring,Blk,Gen 2 |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order