



CWELED-ZW

CLEVERTRONICS LP WEATHERPROOF EXIT



PRODUCT INFORMATION	
Part Number	CWELED-ZW
MIC	AUA02120170001
Description	LP Premium Weatherproof Emergency EXIT
Construction	Polycarbonate clear Cover, Glass reinforced Nylon PA66 Base
Mounting	Wall, ceiling single-sided & ceiling double-sided
Dimensions L x W x H	410mm x 100mm x 272mm
Weight	3.4kg
Operating Mode	Maintained
Testing System	Zoneworks computerised testing
Battery	Lithium Iron Phosphate, 3.2V 1100mAh
Charging Method	Intelligent current limited constant voltage
Diffuser	All directional inserts included in the box
Lamp(s)	6 x LED lamp bar assembly 100,000 hours (AS/NZS2239.3 LSL=47Y/00M)
Operating Voltage	240V AC; 50Hz
Power Consumption	3.3 Watts (Standby), 4.2 Watts (Max)
IP Rating	IP66/IP67
IK Rating	IK10
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =E2.5 C ₉₀ =E2
Viewing Distance	24m
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1550190	BATT:LP 3.2V 1500mAh 390mm lead, no BRKT
8002120	PCA:DLED Cleverfit LightStrip,CT10152-D4
8002323	PCA:CCFLED Driver CT10164-L6 6C50 CTP AU
8001450	PCA:Powerline Node ZW, #CT10310-A6

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.