

Product data sheet Characteristics

1260B20

Machined Brass, Clipsal - Cable Management, 20mm Brass Lock Ring



Main	
Range	Clipsal
Product or component type	Lockring
Accessory / separate part category	Fixing accessory
Range compatibility	Clipsal

Brass

Complementary

Diameter	External: 24 mm Thread: 20 mm
Height pitch dimension	1.5 mm
Thickness	5 mm

Material

Packing Units

Number of Units in Package 1 1 Package 1 Height 0.5 cm Package 1 Width 2.4 cm Package 1 Length 2.4 cm Package 1 Weight 7.6 g Unit Type of Package 2 BB1 Number of Units in Package 2 200 Package 2 Height 7.6 cm Package 2 Width 12 cm	
Package 1 Width 2.4 cm Package 1 Length 2.4 cm Package 1 Weight 7.6 g Unit Type of Package 2 BB1 Number of Units in Package 2 200 Package 2 Height 7.6 cm	
Package 1 Length Package 1 Weight 7.6 g Unit Type of Package 2 Number of Units in Package 2 Package 2 Height 7.6 cm	
Package 1 Weight 7.6 g Unit Type of Package 2 BB1 Number of Units in Package 2 200 Package 2 Height 7.6 cm	
Unit Type of Package 2 BB1 Number of Units in Package 2 200 Package 2 Height 7.6 cm	
Number of Units in Package 2 200 Package 2 Height 7.6 cm	
Package 2 Height 7.6 cm	
Package 2 Width 12 cm	
Package 2 Length 15.8 cm	
Package 2 Weight 1.61 kg	

Offer Sustainability

Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	☑REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EV RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	€Yes
China RoHS Regulation	☑ China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intellability of these products for specific user applications. It is the douwn party such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental Disclosure Product Environmental Profile Circularity Profile No need of specific recycling operations

2