

Product data sheet

Characteristics

2D4P5IPV3B-BU

Clipsal Actassi, LAN Cable, 305m, Category 5E, UTP



Main

Range of product	Titanium
Product brand	Clipsal
Colour	External sheath: blue

Complementary

Communication network category	5e
AWG gauge	AWG 24
Cable shielding type	UTP
Cable insulation material	PVC (polyvinyl chloride)
Material	Conductor: bare copper
Diameter	0.51 mm (conductor)
External diameter	5 mm
Length	305 m
Colour code	BU

Environment

Ambient air temperature for operation	75 °C
Flame retardance	CM
Standards	ANSI/TIA/EIA-568-B ISO/IEC 11801

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.0372 cm
Package 1 Width	0.0198 cm
Package 1 Length	0.0368 cm
Package 1 Weight	0.032 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile