

Product data sheet Characteristics

3043HSUSB-VW

Clipsal Iconic, 3 USB Charger, Type A, 2.1 A, 240 V, Vivid White





Main

Range	Clipsal Iconic
Product or component type	USB charger
[Ue] rated operational voltage	220/240 V AC 50 Hz
Integrated connection type	3 USB 2.0 type A 5 V DC, maximum load current: 2.1 A
Maximum load current with 2 outputs used simultaneously	4.5 A

Complementary

Device mounting	Flush
Device presentation	Complete product
Colour tint	Vivid white (VW)
Surface finish	Matt Textured
Fixing mode	By screws
Type of packing	Polybag
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-550 °C
Relative humidity	1595 %
Protection type	Short time short-circuit protection
Number of terminals	3 screw terminal
Screwdriver shape	Square drive no 1 (SQ1) Philips No 2
Clamping connection capacity	4 x 2.5 mm² for stranded cable(s) 4 x 2.5 mm² for flexible cable(s) 4 x 2.5 mm² for rigid cable(s)
Wire stripping length	16 mm
Height	78 mm
Width	70 mm
Depth	70 mm
Embedding depth	35 mm

Environment

Product certifications	RCM
Electrical insulation class	Class II
IK degree of protection	IK04
IP degree of protection	IP21

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	167.0 g	
Package 1 Height	5.5 cm	
Package 1 width	9.8 cm	
Package 1 Length	15.1 cm	

Offer Sustainability

oner edetamasmy		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	
China RoHS Regulation	[☑] China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

Life Is On