

Product data sheet Characteristics

30USM-WE

Universal Rocker Switch, Clipsal -Mechanisms, 1-Way/2-Way, 250VAC, 20A



Main

Standard Series Series 30	
Clipsal	
Basic element	
	Series 30 Clipsal

Complementary

Installation Type	Flush
Number Of Switches	1
Local signalling	without
[Ue] rated operational voltage	250 V AC
Rated current	20 A 16 AX, fluorescent lamp
Marking	Without marking
Mounting Type	By screws
Actuator	Rocker
Switch function	1-way 2-way

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.3 cm	
Package 1 Width	2.2 cm	
Package 1 Length	2.9 cm	
Package 1 Weight	10 g	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.