

Product data sheet

Characteristics

418S-BK

PLG TP SD ENTRY 250V 10A IN.PN



Main

| | |
|------------------|-----------------|
| Range of product | Standard Series |
| Product brand | Clipsal |

Complementary

| | |
|-------------------------------------|---|
| [In] rated current | 10 A |
| [Ue] rated operational voltage | 230 V 50/60 Hz conforming to EN 60309-2 |
| Colour | Black |
| Material | Plastic |
| Connections - terminals | Screw terminal |
| Plug, socket, control station shape | Angled |
| Duration | 6 h |

Packing Units

| | |
|------------------------------|--------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 42 g |
| Package 1 Height | 4.9 cm |
| Package 1 width | 7.2 cm |
| Package 1 Length | 10 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |