# Product data sheet Characteristics

## 418S-TR PLG TP SD ENTRY 250V 10A IN.PN





#### Main

Range of product	Standard Series	
Product brand	Clipsal	

### Complementary

Complementary		
[In] rated current	10 A	
[Ue] rated operational voltage	230 V 50/60 Hz conforming to EN 60309-2	
Colour	Transparent	
Material	Plastic	
Connections - terminals	Screw terminal	
Plug, socket, control station shape	Angled	
Duration	6 h	

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	0.05 kg	
Package 1 Height	5.5 cm	
Package 1 width	4.5 cm	
Package 1 Length	5.5 cm	

#### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.