Product data sheet Characteristics

438XHD-TR SOCKET CORD EXTENSION 1.5SQ XHD FLEXIBLE 10A





Main	
Range of product	Standard Series
Product or component type	Socket-outlet
Colour	Transparent
Product brand	Clipsal
Quantity per set	Set of 1
Cover type	Complete housing

Complementary

Colour code	TR	
Marking	Without marking	
Local signalling	Without light indicator	
Fixing mode	By screws	
Material	PVC (polyvinyl chloride)	
[In] rated current	10 A	
[Ue] rated operational voltage	250 V AC	
Depth	71 mm	
Diameter	43 mm	

Environment

Standards	AS/NZS 3112
	AS 3100
	AS 3109
	AS/NZS 3122:approval number S/1

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	58 g	
Package 1 Height	4.5 cm	
Package 1 width	10 cm	
Package 1 Length	10 cm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₽¥Yes	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent or and is not to be used for determining suitability or inhability of these products for specific user applications. It is the dourn aren in integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation	☑ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile