Product data sheet Characteristics

439S15-TR PLUG TOP 3PIN 250V 15A INS.PIN





Main

Range of product	Standard Series
Product brand	Clipsal

Complementary

- Comprehensive		
[In] rated current	15 A	
[Ue] rated operational voltage	230 V 50/60 Hz conforming to EN 60309-2	
Colour	Transparent	
Material	Plastic	
Connections - terminals	Screw terminal	
Plug, socket, control station shape	Straight	
Duration	6 h	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	40 g	
Package 1 Height	5.2 cm	
Package 1 width	7 cm	
Package 1 Length	10.4 cm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.