# Product data sheet Characteristics

## 439SHD-TR PLG TP 3PN 250V 10AH/DFL IN.PN





#### Main

Range of product	Standard Series
Product brand	Clipsal

#### Complementary

[In] rated current	10 A	
[Ue] rated operational voltage	230 V 50/60 Hz conforming to EN 60309-2	
Colour	Transparent	
Material	Plastic	
Connections - terminals	Screw terminal	
Plug, socket, control station shape	Straight	
Duration	6 h	

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	34 g	
Package 1 Height	4.4 cm	
Package 1 width	6.9 cm	
Package 1 Length	10.2 cm	

### Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.