

Product data sheet

Characteristics

563K35

single connector 80A, 500 VAC translucent, 2 x 25mm² or 2 x 35mm² cables



Main

Colour	Housing: transparent
Product brand	Clipsal
Provided equipment	2 x screw

Complementary

Rated voltage	415...500 V AC
Cable cross section	25...35 mm ² solid or flexible 2 without cable end sleeve
Connector type	Screw terminals
Contacts material	Brass
Material	PP (polypropylene): housing Zinc plated steel: screw

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	64.0 g
Package 1 Height	5.3 cm
Package 1 width	2.3 cm
Package 1 Length	5.8 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.