

Product data sheet Characteristics

56SO310L-GY

Surface Socket, Clipsal - 56 Series, IP66, 250V 10A - 2 Flat Pins and Round Earth

Main

Range of product	Series 56
Range	Clipsal - 56 Series
Product brand	Clipsal
Product or component type	Socket-outlet
Device application	Power supply
Colour	Grey (RAL 7035)
Outlet standard deviation	Australian/New Zealand

Complementary

Plug, socket category	Low voltage
Device mounting	Surface
Mounting mode	External mounting
[In] rated current	10 A
[Ue] rated operational voltage	250 V AC 50 Hz conforming to EN 60309-2
Poles description	1P + N + E
Voltage colour	Blue
Duration	6 h
Material	Polycarbonate: cover
Contacts material	Screws: brass
Connections - terminals	Screw terminals 1.56 mm² rigid or stranded cable
Connections - terminals	Screw terminal
Tightening torque	0.8 N.m
Socket number	1
Socket-outlet type	С
Outlet standard	Industrial
Net weight	0.4 kg
Depth	77 mm
Width	101 mm
Height	107 mm
Targeted country	Australia

Environment

IP degree of protection	IP66 conforming to AS 60529
Ambient air temperature for operation	-2575 °C
Standards	AS/NZS 4417.1 AS/NZS 3112

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	8.85 cm	
Package 1 Width	10.35 cm	
Package 1 Length	10.65 cm	
Package 1 Weight	400.0 g	

Offer Sustainability

REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	€Yes	

Life Is On