



Main

Range	C-Bus
Product brand	Clipsal
Product or component type	Occupancy sensor
Device application	Lighting
Sensor type	PIR
Product specific application	Staircase monitoring
Colour	Grey

Complementary

[Ue] rated operational voltage	15...36 V DC
[In] rated current	18 mA
Communication network type	C-Bus 100
Number of channels	1
Type of setting	Light sensitivity adjustable
Light intensity adjustment	1 lux user selectable
Data backed up	Non-volatile memory
Local signalling	LEDstatus:
Timer resolution	1 s
Warm-up time	5 s
Horizontal detection angle	0...110 °
Time delay range	0...1 s (switch-on)
Duty cycle	1090 min
Detection face	Lateral: 12 m Frontal: 18 m
C Bus termination	2 flying leads
Material	Plastic
Device mounting	Surface
Mounting support	Wall Ceiling
Mounting height	2.4 m
Fixing center	84 mm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Width	74 mm
Height	111 mm
Depth	138 mm
Colour code	GY

Environment

IP degree of protection	IP66
Ambient air temperature for operation	0...45 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	340 g
Package 1 Height	12.6 cm
Package 1 width	17.6 cm
Package 1 Length	24.8 cm

Offer Sustainability

EU RoHS Directive	Under investigation
Circularity Profile	End of Life Information