

## Product data sheet Characteristics

## 5754ODPE

C-Bus Control and Management System, Passive Infrared, Occupancy and Light Level Sensor Surface Mount, 360deg





Main	
Range	C-Bus
Product brand	Clipsal
Product or component type	Occupancy and light level sensor
Device application	Lighting
Product specific application	Staircase monitoring
Sensor type	PIR
Colour	White

## Complementary

Complementary	
Protection type	Creep zone protection
Type of setting	Light sensitivity adjustable
Number of channels	1
Time delay range	01 s (switch-on)
Detection face	Lateral: 4.85 m Frontal: 4.85 m
Movement detection area	9.7 m
Horizontal detection angle	0360 °
Duty cycle	1080 min
Material	Plastic
Device mounting	Surface
Mounting height	2.7 m

## **Packing Units**

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.0 cm
Package 1 Width	10.1 cm
Package 1 Length	10.1 cm
Package 1 Weight	116.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	20
Package 2 Height	16.0 cm
Package 2 Width	28.0 cm
Package 2 Length	33.5 cm
Package 2 Weight	2.747 kg
Unit Type of Package 3	P12
Number of Units in Package 3	960
Package 3 Height	80.0 cm
Package 3 Width	120.0 cm

Package 3 Length	110.0 cm	
Package 3 Weight	140.856 kg	
Offer Sustainability		
Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant E EU RoHS Declaration	

EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

2