

Product data sheet Characteristics

CLP5015WBZ

Micro Module Blind Controller, Wiser, 4 A, 220-240 V AC, 50Hz, Grey





Main	
Range compatibility	Wiser hub Clipsal Iconic push-button Pro Series push-button
	Saturn Series 4000 push-button Impress Series 30 push-button
Product brand	Clipsal

Connected shutter control

Iconic

Product or component type

Range

Complementary

Device presentation	Module
Technology type	Electronic
Switch additional information	Mechanical and electrical interlock between up/down
Load type	Motor: 500 W at 230 V AC
[Ue] rated operational voltage	220240 V AC 50 Hz
Rated current	4 A
Cos phi	0.61
Standby consumption	Max. 0.4 W
Protection type	Circuit breaker 16 A
Colour tint	Grey
Control type	Push-button By mobile application
Software name	Wiser by SE App
Cable length	NYM cable: 50 m
Communication network type	Wireless Zigbee (24052480 MHz), 10 mW
System requirements	Android 5.1 or higher Wiser App Apple iOS 10.3 or higher Wiser App Bluetooth 4.1 or higher Bluetooth Wiser Home Touch Wiser Home control
Connected auxiliaries	Maximum 10 auxiliary push-buttons
Wiring configuration	3 wires with neutral
Connections - terminals	Screw terminal
Clamping connection capacity	1 x 1.52 x 2.5 mm² for solid cable(s) 1 x 1.52 x 2.5 mm² for stranded cable(s)
Tightening torque	0.5 N.m
Mounting support	Installation box Wall
Type of installation	Indoor installation
Ambient air temperature for operation	035 °C
IP degree of protection	IP20
Relative humidity	590 % non-condensing
Embedding depth	70 mm
Depth	22 mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.

This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.

It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Width	43 mm	
Height	43 mm	
Product certifications	Zigbee 3.0	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	76.0 g
Package 1 Height	5.2 cm
Package 1 width	7.5 cm
Package 1 Length	7.5 cm
Unit Type of Package 2	S02
Number of Units in Package 2	40
Package 2 Weight	3.52 kg
Package 2 Height	15.0 cm
Package 2 width	30.0 cm
Package 2 Length	40.0 cm
Unit Type of Package 3	P06
Number of Units in Package 3	640
Package 3 Weight	71.32 kg
Package 3 Height	75.0 cm
Package 3 width	60.0 cm
Package 3 Length	80.0 cm

Offer Sustainability

Offer Sustamability		
Sustainable offer status	Green Premium product	
REACh Regulation		
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	[™] China RoHS Declaration	
Environmental Disclosure		
Circularity Profile	End Of Life Information	

Life Is On