

Product data sheet

Characteristics

MX9C136340

Clipsal MAX9, Contactor, 4 NO, 63A,
 U_e=415VAC, U_c=240VAC, 3 Modules



Main

Range	MAX9
Product or component type	Contacteur
Device application	Control circuit
Poles description	4P
[I _e] rated operational current	63 A AC-7A
Pole contact composition	4 NO
Network type	AC
Utilisation category	AC-7A
Control type	Remote control
[U _c] control circuit voltage	240 V AC 50 Hz

Complementary

Network frequency	50 Hz
[U _e] rated operational voltage	415 V AC 50 Hz
Maximum power	2.1 W at 415 V AC 50 Hz
[U _i] rated insulation voltage	500 V AC 50 Hz conforming to EN 61095
[U _{imp}] rated impulse withstand voltage	2.5 kV
Switching frequency	100 switching operations/day
Hold-in power consumption in VA	6.5 VA
Inrush power in VA	53 VA
Mounting mode	Clip-on
Mounting support	35 mm symmetrical DIN rail
Comb busbar and distribution block compatibility	NO
9 mm pitches	6
Height	81 mm
Width	54 mm
Depth	63 mm
Net weight	380 g
Colour	White (RAL 9003)
Mechanical durability	1000000 cycles
Electrical durability	100000 cycles 240 V 25 A AC 50 Hz
Connections - terminals	Power: tunnel type terminal1 cable(s) 6...16 mm ² flexible Power: tunnel type terminal2 cable(s) 6...10 mm ² flexible Power: tunnel type terminal1 cable(s) 6...25 mm ² rigid Power: tunnel type terminal2 cable(s) 6...10 mm ² rigid Control: tunnel type terminal1 cable(s) 0.5...4 mm ² flexible Control: tunnel type terminal2 cable(s) 0.5...2.5 mm ² flexible Control: tunnel type terminal1 cable(s) 0.5...6 mm ² rigid Control: tunnel type terminal2 cable(s) 0.5...2.5 mm ² rigid
Tightening torque	Power: 3.5 N.m Control: 0.8 N.m
Wire stripping length	14 mm
Product compatibility	No auxiliary

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Market segment	Residential
Temperature derating table	40 °C (63 A) 50 °C (59.8 A) 60 °C (50 A)

Environment

Quality labels	RCM
Noise level	30 dB
Heat dissipation	28 W at 50 Hz
IP degree of protection	IP20 (modular enclosure) conforming to IEC 60529
Pollution degree	2
Overvoltage category	III
Tropicalisation	Severity B
Relative humidity	95 % at 55 °C
Operating altitude	2000 m
Ambient air temperature for operation	-5...70 °C
Ambient air temperature for storage	-40...70 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.6 cm
Package 1 Width	11.1 cm
Package 1 Length	12.1 cm
Package 1 Weight	410.5 g
Unit Type of Package 2	S03
Number of Units in Package 2	28
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	11.994 kg
Package 3 Height	11.6 cm

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	7-year
----------	--------