

Product data sheet

Characteristics

P3025-XW

Pro Series, switched socket, 2 switch & 2 socket, horiz, 10 A, White



Main

| | |
|----------------------------|---------------------|
| Range | Pro Series |
| Product or component type | Switched socket |
| Device presentation | Complete product |
| Outlet poles configuration | 2P + E with shutter |
| Outlet standard | Australian |

Complementary

| | |
|--------------------------------|---|
| Device mounting | Flush |
| Number of power socket outlets | 2 |
| Number of rocker | 2 |
| Range compatibility | Pro Series |
| Outlet standard description | With earthing contact |
| Outlet standard | Australian/New Zealand |
| Ground lug position | Straight 180° position |
| Fixing mode | By screws |
| Installation direction | Horizontal |
| Colour | White (XW) |
| Surface finish | Glossy |
| Surface treatment | Untreated |
| Type of packing | Polybag |
| Quantity per set | Set of 10 |
| Sale per indivisible quantity | 1 |
| Rated current | 10 A at 250 V AC 50 Hz |
| Connections - terminals | 3 screw terminals |
| Screwdriver shape | Square drive no 1 (SQ1) Philips No 2 |
| Clamping connection capacity | 1 x 2.5...4 x 2.5 mm ² for rigid or stranded cable(s) 3 x 4 mm ² for rigid or stranded cable(s) |
| Wire stripping length | 16 mm |
| Material | PC (polycarbonate): fixing frame PP (polypropylene) POM (polyoxymethylene): shutter PC (polycarbonate): window ABS (acrylonitrile butadiene-styrene): infill piece ABS (acrylonitrile butadiene-styrene): skin |
| Height | 78 mm |
| Width | 116 mm |
| Depth | 27 mm |
| Net weight | 0.094 kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

| | |
|---------------------------------------|------------|
| Ambient air temperature for operation | 0...45 °C |
| Relative humidity | 10...95 % |
| Standards | AS/NZ 3112 |
| Product certifications | RCM |
| IK degree of protection | IK08 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Weight | 97.53 g |
| Package 1 Height | 3.8 cm |
| Package 1 width | 7.8 cm |
| Package 1 Length | 11.6 cm |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |