Product data sheet Characteristics

RCBE216/30S RCBO, Resi MAX, 1PN, C, 16A, 1PN, 30mA, A, SLIM





Range Resi MAX Product or component Residual current breaker with overcurrent protection (RCBO) type Product brand Clipsal Device application Distribution 1P + N Poles description Neutral position Left Number of modules 1 Number of protected 1 poles [In] rated current 16 A AC Network type

Trip unit technology Thermal-magnetic Curve code Earth-leakage sensitivity Earth-leakage protection class Breaking capacity AC Thermal-magnetic C Thermal-magnetic Thermal-magnetic Thermal-magnetic AC Thermal-magnetic Thermal-mag

Complementary

[Ue] rated operational voltage	240 V AC	
Control type	ON/OFF locking with trip free mechanism	
Local signalling	ON/OFF indication	
Mounting mode	Clip-on	
Mounting support	DIN rail	
Size	92.5 x 18 x 71.5 mm conforming to DIN 43880	

Main

Environment

Standards	AS/NZS 61009
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529

Packing Units

PCE	
1	
140.0 g	
6.6 cm	
2.2 cm	
9.8 cm	
	1 140.0 g 6.6 cm 2.2 cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or these products for specific user applications.
This characteristic is not intended to a performe the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Green Premium product	
REACh Declaration	
Compliant EPEU RoHS Declaration	
Yes	
₫Yes	
☑ China RoHS Declaration	
Product Environmental Profile	
	Compliant E EU RoHS Declaration Yes Yes China RoHS Declaration