# RCD440/30

Residual current circuit breaker, Resi MAX, 4P, 40 A, 415 V, 30 mA, AC type





Main	
Range	Resi MAX
Product or component type	Residual current circuit breaker (RCCB)
Product brand	Clipsal
Device application	Protection
Poles description	4P
Number of modules	4
[In] rated current	40 A
Network type	AC
Earth-leakage sensitivity	30 mA
Earth-leakage protection class	Type AC

#### Complementary

[Ue] rated operational voltage	415 V AC	
[Uimp] rated impulse withstand voltage	6 kV	
Size	81 x 72 x 75 mm conforming to DIN 43880	

## Environment

Standards	AS/NZS 61008
IP degree of protection	IP20 conforming to IEC 60529 IP40 (modular enclosure) conforming to IEC 60529
Ambient air temperature for operation	-540 °C

#### **Packing Units**

PCE	
1	
366.0 g	
8 cm	
8 cm	
9 cm	
	1 366.0 g 8 cm 8 cm

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EPEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.