

Product data sheet

Characteristics

RJ6U24PPC

Clipsal Patch Panel Flat 19" 1U 24-port Keystone UTP Loaded Cat6 Non-shutter



Main

Range of product	Actassi
Product brand	Clipsal
Product or component type	Patch panel
Device application	Punch down tool Quick termination tool
Device presentation	Loaded
Provided equipment	Side cover 2 6 U/UTP inside the enclosure Label holder 3 inside the rack Removable cable tray 1 Ports identification at the rear 24 With RJ45 connectors 24
Colour	Grey (RAL 7040)
Colour code	TIA-568A/B
Quantity per set	Set of 1

Complementary

[In] rated current	1.5 A at 25 °C
Dielectric strength	1000 V
Connections - terminals	IDC
Connector type	24 RJ45 Cat. 6 U/UTP
AWG gauge	AWG 24...AWG 23
Cable outer diameter	0.9...1.4 mm
Cable shielding type	U/UTP
Communication network category	6
Communication port support	Ethernet
Contact resistance	20 mOhm
Insulation resistance	>= 500 MOhm
Mounting support	19" rack
Minimum number of matings	750 cycles
Number of rack unit	1U
Number of pairs	4 pairs
Installation direction	90°
Type of connector	S-110 keystone
Material	ABS + PC + metal TIA-568A/B 1.5 mm
Width	482 mm
Depth	124 mm
Height	44 mm
Net weight	1 kg

Environment

Ambient air temperature for operation	-10...60 °C
Ambient air temperature for storage	-20...70 °C
Relative humidity	0...93 %
Standards	ISO/IEC 11801:2011 Ed.2.2 ANSI/TIA-568-C.2 IEC 60603-7-2 AS/NZS 3080:2003 UL 1863
Product certifications	UL listed conforming to UL 94 V0 RCM

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	1090.0 g
Package 1 Height	51.0 mm
Package 1 width	130.0 mm
Package 1 Length	500.0 mm

Offer Sustainability

EU RoHS Directive	Under investigation
Environmental Disclosure	 Product Environmental Profile