## Product data sheet Characteristics

# WSCF227/2-RG SWITCHED SOCKET TWIN WEATHER PROTECTED 10A 250V





#### Main

Range of product	Weathershield	
Product brand	Clipsal	
Colour	Resistant grey	

#### Complementary

Control type	Sliding type ON/OFF button	
Number of gangs	2 gangs	
Pin number	3	
Number of power socket outlets	2	
Fixing mode	By screws	
Local signalling	Without light indicator	
Mounting position	Horizontal	
Material	Plastic	
[Ue] rated operational voltage	250 V AC	
[In] rated current	10 A	
Depth	55 mm	
Length	115 mm	
Width	82 mm	
Fixing center	84 mm	

#### Environment

IP degree of protection	IP53
Standards	AS/NZS 3112:approval number S/1

### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	220 g	
Package 1 Height	8.4 cm	
Package 1 width	8.8 cm	
Package 1 Length	12.2 cm	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Green Premium product
☐ REACh Declaration
Yes
Compliant EPEU RoHS Declaration
Yes
Yes
€Yes
China RoHS Declaration
Product Environmental Profile