



Thread Diameter	Zinc Plated	Hot Dip Galvanised	Stainless Steel
M6	B1006Z	B1006H	B1006S
M8	B1007Z	B1007H	B1007S
M10	B1008Z	B1008H	B1008S
M12	B1010Z	B1010H	B1010S

To fit all 41 mm high channels.

Channel Nut with Long Spring



Thread Diameter	Zinc Plated	Hot Dip Galvanised	Stainless Steel
M6	B4006Z	B4006H	B4006S
M8	B4007Z	B4007H	B4007S
M10	B4008Z	B4008H	B4008S
M12	B4010Z	B4010H	B4010S

To fit all 21 mm high channels.

Channel Nut with Short Spring

Channel Type	Nut Type	Pullout kN	Slip kN	Torque Nm
B1000	B1006	7.3	2.7	9
	B1007	10.1	5.2	22
	B1008	16.5	8.7	44
	B1010	16.5	12.9	77
B2000	B1006	4.8	1.1	9
	B1007	5.0	4.0	22
	B1008	10.8	7.1	37
	B1010	10.8	6.7	37
B3300	B4006	7.3	2.7	9
	B4007	10.1	5.2	22
	B4008	16.5	8.7	37
	B4010	16.5	12.9	37
B4000	B4006	4.8	1.1	9
	B4007	5.0	4.0	22
	B4008	10.8	7.1	37
	B4010	10.8	6.7	37

Note Slip and Pullout ratings are based on using grade 4.6 commercial screws.

Slip and Pullout Information