


FLEXION G2 5M KIT

FX25W5M4K-IP20

SAP CODE: 2002015




4000K, IP20, 25W total, 5W/m, 5m, Flexible strip kit, Cut points at 100mm intervals with 60 diodes per meter

A premium high CRI LED strip with flexible cut points for indoor use and feature lighting.



Photometric Diagram



Unit: cd
C0/180 117.6deg

KEY INFORMATION

| | |
|-------------------------|-----------------|
| Lumen Output (p/metre) | 533lm/m |
| Lumen Output | 2670lm |
| Input Power | 5W/m |
| Install | SURFACE/DS TAPE |
| Driver Type | Non-Dimmable |
| Fitting Colour | WHITE |
| Warranty | 5yr |
| IP Rating | IP20 |
| Rebate Scheme Approvals | N/A |
| Cut Interval | 100mm |

PHOTOMETRIC

| | |
|------------|---------|
| Efficacy | 107lm/W |
| LED | SMD |
| CCT | 4000K |
| CRI | >90 |
| Beam Angle | 120° |

ELECTRICAL

| | |
|-----------------------------|-------------------|
| Driver | Remote |
| Supply Input | 220-240V, 50/60Hz |
| Driver Output Voltage | 24V DC |
| Power Factor | >0.9 |
| LED Input Current (nominal) | 1050mA |
| Useful life @Ta25° (L70) | 50,000hr |

CONSTRUCTION

| | |
|---------------------------|---------------------------------|
| Fixings/Hardware | Self Adhesive Backing & Saddles |
| Connection Type | 1m Flex & Plug |
| Total Weight | 0.46kg |
| Dimensions | 5000 x 10 x 2mm |
| Operating Ambient Temp. | -20 to 45°C |
| Electrical Classification | Class 2 |