



STAX 10W

STAX10WB5K

SAP CODE: 2001647



Photometric Diagram



Unit: cd
 - C0/180 110.0deg
 - C90/270 110.0deg

10W, Slimline LED floodlight

A compact and stylish LED floodlight for general area lighting.

KEY INFORMATION

Lumen Output	1040lm
Input Power	10W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	Non-Dimmable
Trim Colour	BLACK
Warranty	3yr
IP Rating	IP65
IK Rating	IK07
IC Rating	N/A
Rebate Scheme Approvals	

PHOTOMETRIC

Efficacy	104lm/W
LED	SMD
CCT	5000K
CRI	>80
Beam Angle	110°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	N/A
Power Factor	>0.9
LED Input Current (nominal)	N/A
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Aluminium + Polycarbonate
Optics	Polycarbonate Diffuser
Adjustable Angle	0-180°
Fixings/Hardware	Bracket
Connection Type	1m Flex
Total Weight	0.3kg
Dimensions	164 x 113 x 32mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1