



STAX 50W

STAX50WB5K

SAP CODE: 2001650



Photometric Diagram



Unit: cd
 - C0/180 110.0deg
 - C90/270 110.0deg

50W, Slimline LED floodlight

A compact and stylish LED floodlight for general area lighting.

KEY INFORMATION

| | |
|-------------------------|----------------------|
| Lumen Output | 5640lm |
| Input Power | 50W |
| Hole Cutout Size | N/A |
| Install | SURFACE MOUNT |
| Dimming Options | Non-Dimmable |
| Trim Colour | BLACK |
| Warranty | 3yr |
| IP Rating | IP65 |
| IK Rating | IK08 |
| IC Rating | N/A |
| Rebate Scheme Approvals | |

PHOTOMETRIC

| | |
|------------|---------|
| Efficacy | 113lm/W |
| LED | SMD |
| CCT | 5000K |
| CRI | >70 |
| Beam Angle | 110° |

ELECTRICAL

| | |
|-----------------------------|-------------------|
| Driver | Integral |
| Supply Input | 220-240V, 50/60Hz |
| Driver Output Voltage | 80VDC |
| Power Factor | >0.9 |
| LED Input Current (nominal) | 650mA |
| Useful life @Ta25° (L70) | 50,000hr |

CONSTRUCTION

| | |
|---------------------------|------------------------|
| Housing | Aluminium 6063 |
| Optics | Polycarbonate Diffuser |
| Adjustable Angle | 0-180° |
| Fixings/Hardware | Bracket |
| Connection Type | 1m Flex |
| Total Weight | 1kg |
| Dimensions | 244 x 183 x 37mm |
| Operating Ambient Temp. | -20 to 45°C |
| Electrical Classification | Class 1 |