





Cable Management







Cable Clips

Long-lasting, wire management clips

Module Frame Clips

	Part No.	Length (mm)	Width (mm)	Height (mm)	Wire
	ACC	16.85	10.00	10.00	1-2 PV wire Wire diameter: min 4.1mm / max 6.7mm Module thickness range: 1.5-2.5mm
	ACC-PV	18.42	10.00	12.60	1-2 PV wires Wire diameter: min 4.1mm / max 7.49mm Module thickness range: 1.5-2.5mm
	ACC-FLD	19.00	10.00	12.70	1-2 PV wire Wire diameter: min 4.1mm / max 7.49mm Module thickness range: 1.5-2.5mm
	ACC-FPV	23.33	12.50	14.22	1-2 PV wire Wire diameter: min 4.1mm / max 8.50mm Module thickness range: 1.3-3.5mm

90° Module Frame Clips

	Part No.	Length (mm)	Width (mm)	Height (mm)	Wire
	ACC-F90-1	20.58	13.08	14.22	1-2 PV wire Wire diameter: min 4.1mm / max 7.49mm Module Thickness Range: 1.5-2.5mm
	ACC-F2-90	29.49	10.51	15.10	1-2 micro inverter trunk cables or 1-2 AC cables Wire diameter: 1 wire - min 4.1mm / max 14mm or 2 wires - min 4.1mm / max 11mm
	ACC-F4-90	34.72	10.51	14.31	1-4 wires PV wires Wire diameter: min 4.1mm / max 7.49mm Module thickness range: 1.5-2.5mm
	ACC-F1-270	23.50	10.00	19.55	2 PV wires or 1 Micro Inverter Trunk Wire diameter: min 4.1mm / max 14mm Module thickness range: 1.5-2.5mm

Installation examples



ACC-FPV
198



ACC-F90-1



ACC-F90-1