

TECHNICAL DATA SHEET



Dy-Mark (Aust) Pty Ltd
PO Box 1556 Toowong 4066
Phone: 1300 396 275 Fax: 1300 360 440
www.dymark.com.au

Dy-Mark SPRAY & MARK® WATER-BASED



Dy-Mark Spray & Mark Water-Based is a high quality, fast drying water-based acrylic marking paint which utilises a 360° valve for any angle application. Its specially developed water-based formula has a low odour and lower toxicity. **Spray & Mark Water-Based** is ideal for use in construction, landscaping and civil works applications. **Spray & Mark** is suitable for use with the **Long Arm Handle** and **2-Wheel Spot Marking Handle**, also available from Dy-Mark.

DIRECTIONS FOR USE

Suitable Surfaces:

Concrete, bitumen, steel, timber, polystyrene foam and grass.

Ideal Application Temperature:

Between 5°C and 40°C. Avoid use in windy conditions.

Before Spraying:

Shake can for at least 45 seconds **AFTER** the mixing ball begins to rattle. Shake the can occasionally during use.

Application:

Hold the can **UPRIGHT** or in the **INVERTED** position and spray approximately 10-15cm from the surface. Adjust the spray width by moving closer or further away from the surface to be sprayed.

Coverage:

Will produce 200+ 'X' marks, up to 120 linear metres (depending on surface and colour used).

Drying Time:

Touch dry in 5 minutes at 25°C.

Drying will be slower in cold and humid conditions, in the absence of ventilation or where heavy film build is applied.

Caution:

Painted surfaces may become slippery when wet. Refer to disclaimer on page 3.

TECHNICAL DATA SHEET

Dy-Mark (Aust) Pty Ltd
PO Box 1556 Toowong 4066
Phone: 1300 396 275 Fax: 1300 360 440
www.dymark.com.au



TECHNICAL DATA

Size:	350g Aerosol
Colour:	4 Standard and 3 Fluoro colours
Finish:	Matt
Consistency:	Liquid
Propellant:	Dimethyl Ether
Resin:	Acrylic
VOC:	<595g/L

STORAGE

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C. Store in a well-ventilated place.

Extremely flammable aerosol. May burst if heated. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

Never leave aerosols inside a car, ie on dashboards and in boots or in any other enclosed vehicle. The internal temperature of the vehicle can be up to 30°C hotter than the outside temperature.

If an aerosol is kept near a heat source, the pressure in the can increases rapidly to levels that exceed the can design limits and may cause the can to burst.

DISPOSAL

Dispose of contents/empty aerosol container according to regional regulations. Spray unwanted paint onto newspaper, allow to dry and dispose of via domestic waste collection. Empty aerosol cans are recyclable via steel can recycling programs.

FIRST AID/SAFETY INFORMATION

Please refer to Safety Data Sheet before use. Safety data sheets are available from our website www.dymark.com.au or from the following QR code:



Contact a POISONS INFORMATION CENTRE: Australia 13 11 26, New Zealand 0800 764 766 or doctor/physician/first aider if you feel unwell.

Intentional misuse by deliberately inhaling contents can be harmful or fatal.

KEEP OUT OF REACH OF CHILDREN.

TECHNICAL DATA SHEET



Dy-Mark (Aust) Pty Ltd
PO Box 1556 Toowong 4066
Phone: 1300 396 275 Fax: 1300 360 440
www.dymark.com.au

DISCLAIMER

The information provided within this Technical Data Sheet is intended as a guide only. The slip resistance and performance of this product depends on many factors outside the control of Dy-Mark®; including surface preparation, surface-specific conditions, surface types, correct application and environmental conditions.

Dy-Mark® recommends customers undertake their own risk assessment prior to use to determine the suitability of the product for the particular use intended. Some factors to consider:

- Slip resistance required
- Surface type
- Volume of traffic
- Potential exposure to any surface contaminants eg. Water, solvents or chemicals

It is essential that a sample of the product be applied to the intended area of use to ensure it is acceptable in appearance and finish and that it performs on the specific surface.

For further information please contact the Dy-Mark® Sales and Customer Support Centre on 1300 396 275.