


ECO LED Panel Gen 2

ECOPL063CSEG2

- One box solution - 3-in-1 Colour Select option to choose the right colour temperature for the application
- Easy to install - Remote constant current driver with 1.2 meter flex and plug and light-weight design
- Quality opal diffuser - delivering high quality and even light distribution



Performance

System Power	14W
Exit Lumen	1400lm, 1500lm, 1400lm
Efficacy	100lm/W
Tuneable CCT	N/AK to N/AK
CCT	4000K, 5000K, 6500K
CRI	80
Operating Temperature	0°C to 40°C
MacAdam Steps	6SDCM
Ingress Protection Rating	IP40
Beam Distribution	Symmetric
Beam Angle	110°
Warranty	3 Years
Lifetime	105,000hrs (L80/10)

Physical


Dimensions	L595 x W295 x H30mm
Diffuser	Polystyrene
Luminaire Colour	White
Weight	1kg
Luminaire Material	Aluminium (Extruded)
Driver Location	Remote
Finish	Powder Coated
Installation	Recessed

Electrical

Dimming	Non - Dimmable
Voltage	240V
Line Voltage Frequency	50Hz
Inrush Current	2A
Inrush Current Duration	33µs
Line Current	0.07A
Electrical Rating	Class II

COLOUR SELECT

Line Drawings



Product Images



Accessories

ECOPLWIREKITG2H	BACKLIT PANEL SUSPENSION KIT 1M Y-SHAPE WIRE 2 BRACKETS
ECOPNLBRKTKIT	ECO PANEL BRKT KIT (4) & SCREWS
FRM/PM18W	Plaster frame to mount in plaster ceiling - White, 600x300mm
FRM/PM18WIDE	Plaster frame to mount in plaster ceiling - White, 600x600mm
FRM/PM36W	Plaster frame to mount in plaster ceiling - White, 1200x300mm
FRM/PM36WIDE	Plaster frame to mount in plaster ceiling - White, 1200x600mm
UDFRM/12-3	Universal Deep Frame 1200x300mm
UDFRM/12-6	Universal Deep Frame 1200x600
UDFRM/6-3	Universal Deep Frame 600x300mm
UDFRM/6-6	Universal Deep Frame 600x600

Product Images

