

Nipper LED Batten

NIPBAT404ECSLS

- Designed with a wide 130mm width base to easily replace old and energy consuming twin fluorescent battens.
- Flicker free LED driver built-in for increased visual acuity and comfort
- Option for emergency with Lithium Iron Phosphate Battery 2.5w @ 350lumen available




LUMEN SELECT[®] | COLOUR SELECT

Performance

System Power	36W, 36W, 36W, 30W, 30W, 30W, 25W, 25W, 25W, 18W, 18W, 18W
Exit Lumen	3860lm, 4000lm, 3630lm, 3300lm, 3450lm, 3160lm, 2890lm, 2990lm, 2740lm, 2200lm, 2330lm, 2160lm
Efficacy	107lm/W, 111lm/W, 100lm/W, 110lm/W, 115lm/W, 105lm/W, 115lm/W, 119lm/W, 109lm/W, 122lm/W, 129lm/W, 120lm/W
CCT	4000K, 5000K, 6500K, 4000K, 5000K, 6500K, 4000K, 5000K, 6500K, 4000K, 5000K, 6500K
CRI	80
Operating Temperature	0°C to 40°C
MacAdam Steps	5SDCM
Ingress Protection Rating	IP20
Beam Angle	120°
Lifetime	54,000hrs (L80/50)

Line Drawings



Product Images



Physical

Dimensions	L1230 x W130 x H74mm
Diffuser	Polycarbonate
Luminaire Colour	White
Weight	2kg
Luminaire Material	Steel (Mild)
Driver Location	Integrated
Finish	Powder Coated
Installation	Surface Mounting

Electrical

Dimming	Non - Dimmable
Voltage	240V
Line Voltage Frequency	50Hz/60Hz
Inrush Current	20A
Inrush Current Duration	350µs
Line Current	0.15A
Electrical Rating	Class 1