

Nipper Diffused Batten

PND136EL

- Wide body, stylish smooth lined linear diffused electronic batten
- Diffuser can be removed without removing end cap
- Standard integral electronic ballast



Performance

| System Power | 38W |
|---------------------------|-------------|
| Exit Lumen | 2806lm |
| Efficacy | 73lm/W |
| CCT | 4000K |
| CRI | 85 |
| Operating Temperature | 0°C to 25°C |
| Ingress Protection Rating | IP20 |
| Warranty | 1 Years |
| | |


Physical

| - | |
|--------------------|-------------------------|
| Dimensions | L1229 x W52 x H97mm |
| Reflector | Aluminium |
| Diffuser | Acrylic |
| Luminaire Colour | White |
| Weight | 3kg |
| Luminaire Material | Steel (Mild) |
| Finish | Powder Coated |
| Installation | Ceiling Surface Mounted |
| | |

Electrical

| Voltage | 240V |
|-------------------|---------|
| Electrical Rating | Class 1 |

Line Drawings



*Rated LED design life where stated is based upon application of Pierlite's operating and maintenance guidelines; see pierlite.com.au. Actual product life may vary dependent upon frequency of maintenance and product application. Due to continual product improvement, information is subject to change without notification. Gerard Lighting Pty Ltd standard Terms and Conditions apply

Pierlite is a registered trademark of Gerard Lighting Pty Ltd @Copyright Pierlite 2020