

VandaLED

VANDALED25D

- Quality LEDs in white 4000K
- Two energy efficient options 12W 350mA 1225lms & 25W 700mA 2252lms
- Lower maintenance costs due to the LEDs 50,000 hour average life.



System Power	25W
Exit Lumen	2252lm
Efficacy	90lm/W
ССТ	4000K
CRI	80
Operating Temperature	-20°C to 50°C
MacAdam Steps	3SDCM
Ingress Protection Rating	IP65
Impact Rating	IK10
Warranty	5 Years
Lifetime	50,000hrs (L70/B50)

Physical


Dimensions	L600 x W70 x H85mm
Diffuser	Polycarbonate
Luminaire Colour	Grey (Light)
Weight	1kg
Luminaire Material	Aluminium (Die Cast)
Driver Location	Integrated
Heatsink	Aluminium (Die Cast)
Finish	Powder Coated
Installation	Ceiling Surface Mounted

Electrical

Voltage	240V
Line Current	0.10A
Electrical Rating	Class 1



Line Drawings



*Rated LED design life where stated is based upon application of Pierlite's operating and maintenance guidelines; see pierlite.com.au. Actual product life may vary dependent upon frequency of maintenance and product application. Due to continual product improvement, information is subject to change without notification. Gerard Lighting Pty Ltd standard Terms and Conditions apply

Pierlite is a registered trademark of Gerard Lighting Pty Ltd @Copyright Pierlite 2020