



3P 63A Switch , Red Toggle

SBR364

Architecture

| | |
|------------------|-----------------|
| Type of order | Break switch |
| Neutral position | without neutral |
| Number of poles | 3 P |
| Type of pole | 3 P |

Main electrical features

| | |
|------------------------------|----------|
| Rated operational voltage Ue | 400 V |
| Frequency | 50/60 Hz |

Voltage

| | |
|---------------------------------|--------|
| Rated insulation voltage | 440 V |
| Type of voltage input 1 | AC |
| Rated impulse withstand voltage | 6000 V |

Electric current

| | |
|---|----------|
| Rated operational current in AC21 category B | 63 A |
| Acceptable current rating with AC22 category A | 63 A |
| Rated current | 63 A |
| Rated short-time withstand current 1s | 0,945 kA |
| Thermal rated current outside of housings | 63 A |
| Rated operational current in AC21 category A | 63 A |
| Acceptable current rating with AC22 category B | 63 A |
| Rated short-circuit making capacity Icm under 415V AC according IEC 60947-3 | 1332 A |

Frequency

| | |
|-----------|-------------|
| Frequency | 50 to 60 Hz |
|-----------|-------------|

Power

| | |
|---------------------------|-------|
| Total power loss under IN | 6,6 W |
| Power loss per pole at In | 2,2 W |

Endurance

| | |
|---|-------|
| Electrical durability at nominal load in AC21 in operating cycles | 2500 |
| Electrical durability at nominal load in AC22 in operating cycles | 2500 |
| Number of mechanical operations | 40000 |

Dimensions

| | |
|-----------------------------|---------|
| Depth of installed product | 68 mm |
| Height of installed product | 83 mm |
| Width of installed product | 52,5 mm |

Installation, mounting

| | |
|---|-------|
| Tightening torque | 3,6Nm |
| Top removability for modular devices | no |
| Bottom removability for modular devices | yes |

Connection

| | |
|---|-----------------------|
| Connection cross-sect. flexible conductor | 6 / 35mm ² |
| Connection cross-sect. rigid cable | 6 / 50mm ² |
| Cage clamp position | in line |
| Type of connection | with screw |

Equipment

| | |
|---------------------------------------|-----|
| Quantity of NO contacts | 3 |
| Can be accessorized | yes |
| With transparent product label holder | yes |

Standards

| | |
|-------------------------|---------------|
| Standard text | IEC 60947-3 |
| European directive WEEE | not concerned |

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Use conditions

| | |
|--|-----------|
| Operating temperature | -20 50 °C |
| Degree of pollution according to IEC 60664 / IEC 60947-2 | 2 |
| Altitude | 2000 m |
| Storage/transport temperature | -40 80 °C |