



## SPD 2P pluggable 8kA ind.

SPN208D

### Architecture

Type of pole	1P+N
--------------	------

### Controls and indicators

Indicator lamp	reserve
----------------	---------

### Main electrical features

Rated operational voltage $U_e$	230 V
Nominal discharge current ( $I_n$ ) 8/20 $\mu$ s, IEC 61643)L-N(PEN)/ N-PE	2 kA

### Voltage

Maximum continuous operating voltage $U_c$	255 V
Voltage protection level $U_p$ according to IEC61643-1	1,5 kV
Voltage protection level $U_p$ L-PE/N-PE according to IEC61643-11	1,5 kV
Voltage level $U_p$ L-N/PEN IEC61643-11	1 kV

### Electric current

Max discharge ( $I_{max}$ ) L-N(PEN)/ N-PE	8 kA
--	------

### Power

Total power loss under $I_N$	0,1 W
------------------------------	-------

### Dimensions

Width of installed product	35 mm
----------------------------	-------

### Connection

Connection cross-sect. flexible conductor	25mm <sup>2</sup>
Connection cross-sect. rigid cable	35mm <sup>2</sup>

**Equipment**

---

With remote signalling contact	no
--------------------------------	----

---

**Standards**

---

European directive WEEE	concerned
-------------------------	-----------

---

**Use conditions**

---

Operating temperature	-40 80 °C
Storage/transport temperature	-40 80 °C

---