



Sm.distr, IC<sup>2</sup>, surface, 6M, transp.door

VD106TT

#### Architecture

Fixing mode	surface-mounting
-------------	------------------

#### Functions

With a pipe-in lead	yes
---------------------	-----

#### Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

#### Main electrical features

Nominal voltage	400 V
-----------------	-------

#### Cover, door

Cover type	Closed (plain)
------------	----------------

Transparent cover or door	yes
---------------------------	-----

Cover type	Door
------------	------

Door locking	without
--------------	---------

Type of door closing	Latch
----------------------	-------

Door leave	single
------------	--------

Door quantity	1
---------------	---

Identification od protection index	40
------------------------------------	----

Interlockable	no
---------------	----

#### Materials

RAL colour	RAL 9010 - Pure white
------------	-----------------------

Colour	white
--------	-------

Colour	pure white
--------	------------

Material	plastic
----------	---------

Type of surface treatment	untreated
---------------------------	-----------

#### Dimensions

Depth of installed product	91 mm
----------------------------	-------

Internal depth	72 mm
----------------	-------

Height of installed product	170 mm
-----------------------------	--------

Width of installed product	134,5 mm
----------------------------	----------

Width in division units	6
-------------------------	---

#### Installation, mounting

Suitable for outdoor use	no
--------------------------	----

#### Accessories included

Mounting plate included	no
With lock	no

#### Equipment

Number of rows	1
Quantity of section in width	1
Can be accessorized	yes
Quantity of rails	1

#### Standards

GWT Glow wire test	650 °C
European directive WEEE	not concerned

#### Safety

Protection class	isol.class II
Protection index IP	IP40
IK protection code against mechanical impacts	IK07
Halogen free	yes
Ultraviolet resistant	no

#### Use conditions

Operating temperature	-25 40 °C
-----------------------	-----------