

8 M Surface mounting enclosure IC2 EGY

VD108PT

Architecture	
Fixing mode	surface-mounting
Functions	
With a pipe-in lead	yes
Compatibility	
Compatible with DIN rail mounting	yes
Main electrical features	
Nominal voltage	400 V
Electric current	
Rated current	80 A
Cover, door	
Type of door closing	Latch
Identification od protection index	40
Interlockable	no
Cover type	Closed (plain)
Door locking	without
Door leave	single
Door quantity	1
Cover type	Door
Transparent cover or door	no
Materials	
Colour	pure white
Colour	white
RAL colour	RAL 9010 - Pure white
Material Type of surface treatment	plastic

Depth of installed product	91 mm	
Internal depth	72 mm	
Height of installed product	170 mm	
Width of installed product	170,5 mm	
Width in division units	8	
Installation, mounting		
Suitable for outdoor use	no	
Accessories included		
Mounting plate included	no	
With lock	no	
Equipment		
Number of rows	1	
Quantity of section in width	1	
Quantity of rails	1	
Can be accessorized	yes	
Extension possible	no	
Standards		
GWT Glow wire test	650 °C	
Safety		
Protection index IP	IP40	
Protection class	isol.class II	
Halogen free	yes	
Ultraviolet resistant	no	
Use conditions		
Operating temperature	-25 40 °C	