



Sm.distr, IC<sup>2</sup>, surface, 8M, transp.door DZA

VD108TT

#### Architecture

Fixing mode	surface-mounting
-------------	------------------

#### Functions

With a pipe-in lead	yes
---------------------	-----

#### Compatibility

Compatible with DIN rail mounting	yes
-----------------------------------	-----

#### Main electrical features

Nominal voltage	400 V
-----------------	-------

#### Cover, door

Cover type	Closed (plain)
Transparent cover or door	yes
Cover type	Door
Door locking	without
Type of door closing	Latch
Door leave	single
Door quantity	1
Identification od protection index	40
Interlockable	no

#### Materials

RAL colour	RAL 9010 - Pure white
Colour	white
Colour	pure white
Material	plastic
Type of surface treatment	untreated

#### Dimensions

Depth of installed product	91 mm
Internal depth	72 mm
Height of installed product	170 mm
Width of installed product	170,5 mm
Width in division units	8

**Installation, mounting**

Suitable for outdoor use	no
--------------------------	----

**Accessories included**

Mounting plate included	no
With lock	no

**Equipment**

Number of rows	1
Quantity of section in width	1
Can be accessorized	yes
Quantity of rails	1

**Standards**

GWT Glow wire test	650 °C
--------------------	--------

**Safety**

Protection class	isol.class II
Protection index IP	IP40
Halogen free	yes
Ultraviolet resistant	no

**Use conditions**

Operating temperature	-25 40 °C
-----------------------	-----------