



Sm.distr, golf, flush, MM, 36M, wh door

VF218PZE

Architecture

Fixing mode	flush-mounting
-------------	----------------

Compatibility

Suitable for lightning protection	no
-----------------------------------	----

Cover, door

Cover type	With Notch
Transparent cover or door	no
Cover type	Door
Material thickness cover	3 mm
Type of door closing	Latch
Door material	Plastic
Door transparent material	Plastic
Door leave	single
Door quantity	1
Identification od protection index	40
Interlockable	no

Materials

RAL colour	RAL 9010 - Pure white
Colour	white
Colour	pure white
Material	plastic
Type of surface treatment	untreated

Dimensions

Insertion depth	72 mm
Depth of installed product	97,5 mm
Depth of wall niche	72 mm
Internal depth	97,5 mm
Height of installed product	418 mm
Built-in width	426 mm
Width of installed product	460 mm
Width in division units	18
Thickness of sidewall material	3 mm

Installation, mounting

Suitable for outdoor use	no
--------------------------	----

Accessories included

Mounting plate included	no
With lock	no

Equipment

Number of units	18
Number of rows	2
Can be accessorized	yes
Extension possible	yes
Quantity of rails	2

Standards

GWT Glow wire test	650 °C
--------------------	--------

Safety

Protection class	isol.class II
Protection index IP	IP40
IK protection code against mechanical impacts	IK07