



Sm.distr, golf, flush, 54M, white door DZA

VF318PT

#### Architecture

|             |                |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

#### Functions

|                     |     |
|---------------------|-----|
| With a pipe-in lead | yes |
|---------------------|-----|

#### Compatibility

|                                   |     |
|-----------------------------------|-----|
| Compatible with DIN rail mounting | yes |
|-----------------------------------|-----|

#### Main electrical features

|                 |       |
|-----------------|-------|
| Nominal voltage | 400 V |
|-----------------|-------|

#### Cover, door

|            |                |
|------------|----------------|
| Cover type | Closed (plain) |
|------------|----------------|

|                           |    |
|---------------------------|----|
| Transparent cover or door | no |
|---------------------------|----|

|            |      |
|------------|------|
| Cover type | Door |
|------------|------|

|              |         |
|--------------|---------|
| Door locking | without |
|--------------|---------|

|                      |       |
|----------------------|-------|
| Type of door closing | Latch |
|----------------------|-------|

|            |        |
|------------|--------|
| Door leave | single |
|------------|--------|

|               |   |
|---------------|---|
| Door quantity | 1 |
|---------------|---|

|                                    |    |
|------------------------------------|----|
| Identification od protection index | 40 |
|------------------------------------|----|

|               |    |
|---------------|----|
| Interlockable | no |
|---------------|----|

#### Materials

|            |                       |
|------------|-----------------------|
| RAL colour | RAL 9010 - Pure white |
|------------|-----------------------|

|        |       |
|--------|-------|
| Colour | white |
|--------|-------|

|        |            |
|--------|------------|
| Colour | pure white |
|--------|------------|

|          |         |
|----------|---------|
| Material | plastic |
|----------|---------|

|                           |           |
|---------------------------|-----------|
| Type of surface treatment | untreated |
|---------------------------|-----------|

#### Dimensions

|                 |       |
|-----------------|-------|
| Insertion depth | 72 mm |
|-----------------|-------|

|                            |         |
|----------------------------|---------|
| Depth of installed product | 97,5 mm |
|----------------------------|---------|

|                |         |
|----------------|---------|
| Internal depth | 97,5 mm |
|----------------|---------|

|                             |        |
|-----------------------------|--------|
| Height of installed product | 543 mm |
|-----------------------------|--------|

|                 |        |
|-----------------|--------|
| Built-in height | 507 mm |
|-----------------|--------|

|                |        |
|----------------|--------|
| Built-in width | 426 mm |
|----------------|--------|

Technical Properties

|                            |        |
|----------------------------|--------|
| Width of installed product | 460 mm |
| Width in division units    | 18     |

**Installation, mounting**

|                          |    |
|--------------------------|----|
| Suitable for outdoor use | no |
|--------------------------|----|

**Accessories included**

|                         |    |
|-------------------------|----|
| Mounting plate included | no |
| With lock               | no |

**Equipment**

|                              |     |
|------------------------------|-----|
| Number of rows               | 3   |
| Quantity of section in width | 1   |
| Can be accessorized          | yes |
| Quantity of rails            | 3   |

**Safety**

|                       |               |
|-----------------------|---------------|
| Protection class      | isol.class II |
| Protection index IP   | IP40          |
| Halogen free          | yes           |
| Ultraviolet resistant | no            |

**Use conditions**

|                       |           |
|-----------------------|-----------|
| Operating temperature | -25 40 °C |
|-----------------------|-----------|