



Sm.distr, golf, surface, 24M, wh door DZA

VS212PT

Architecture

| | |
|-------------|------------------|
| Fixing mode | surface-mounting |
|-------------|------------------|

Functions

| | |
|---------------------|-----|
| With a pipe-in lead | yes |
|---------------------|-----|

Compatibility

| | |
|-----------------------------------|-----|
| Compatible with DIN rail mounting | yes |
|-----------------------------------|-----|

Main electrical features

| | |
|-----------------|-------|
| Nominal voltage | 400 V |
|-----------------|-------|

Electric current

| | |
|---------------|------|
| Rated current | 80 A |
|---------------|------|

Cover, door

| | |
|------------------------------------|----------------|
| Type of door closing | Latch |
| Identification od protection index | 40 |
| Interlockable | no |
| Cover type | Closed (plain) |
| Door locking | without |
| Door leave | single |
| Door quantity | 1 |
| Cover type | Door |
| Transparent cover or door | no |

Materials

| | |
|---------------------------|-----------------------|
| Colour | pure white |
| Colour | white |
| RAL colour | RAL 9010 - Pure white |
| Material | plastic |
| Type of surface treatment | untreated |

Dimensions

| | |
|-----------------------------|--------|
| Depth of installed product | 99 mm |
| Internal depth | 99 mm |
| Height of installed product | 377 mm |
| Width of installed product | 282 mm |
| Width in division units | 12 |

Installation, mounting

| | |
|--------------------------|----|
| Suitable for outdoor use | no |
|--------------------------|----|

Accessories included

| | |
|-------------------------|----|
| Mounting plate included | no |
| With lock | no |

Equipment

| | |
|------------------------------|-----|
| Number of rows | 2 |
| Quantity of section in width | 1 |
| Quantity of rails | 2 |
| Can be accessorized | yes |
| Extension possible | yes |

Standards

| | |
|--------------------|--------|
| GWT Glow wire test | 650 °C |
|--------------------|--------|

Safety

| | |
|---|---------------|
| IK protection code against mechanical impacts | IK07 |
| Protection index IP | IP40 |
| Protection class | isol.class II |
| Halogen free | yes |
| Impact strength | IK07 |
| Ultraviolet resistant | no |

Use conditions

| | |
|-----------------------|-----------|
| Operating temperature | -25 40 °C |
|-----------------------|-----------|