

# **ASTRAL**

**AST10W-115** SAP CODE: 2002425


### Premium, low glare.

The ASTRAL range meets market demands with a complete selection of sizes and optional reflectors to suit every designer's needs. Each variant complies with Greenstar requirements, ensuring high performance for commercial applications. With high lumen outputs, a tight beam angle, tritone, and dimming technology, ASTRAL is the go-to solution for commercial lighting.

#### **APPLICATIONS**

Bathrooms, Boardroom / Meeting Rooms, Cocktail Lounge, Medical Facilities, Hotel Common Areas, Hotel Rooms, Offices, Retail Spaces, Showrooms, Restaurants / Cafes, Entrance, Food Courts

#### **DIMENSION DIAGRAMS**




#### Disclaimer

Note 1: SDCM Values measured on 4K and 5.7K CCT





## PHOTOMETRIC DIAGRAM



Unit: cd - C0/180 63.1deg - C90/270 61.7deg

Photometric diagram shown is for

KEY INFORMATION	
Power	10 W
Lumen Output	1020 / 1070 / 1030 lm
Cutout Size	Ø 90 mm
Mounting Type	Recessed
Dimming Type	Phase-Cut Dimmable (Trailing Edge, 10-100%)
Body Colour	White
IP Rating	IP54 F - IP20 B
IC Rating	IC-4 (Lamp Only)
Operating Ambient Temp.	-20°C to 45°C
Connection Type	0.6m Flex & Plug
Driver	Remote
Warranty	5 yrs

PHOTOMETRIC	
Efficacy	97 / 105 / 100 lm/W
ССТ	4000 / 5000 / 5700 K
CRI	> 90
SDCM	< 3
UGR	< 19
Beam Angle	60°
Flicker-Free	Yes
Projected Lifespan	54.000hrs @ Ta25°C(L80)

ELECTRICAL	
Input Voltage	220-240VAC
Driver Output Voltage	30-40V DC
Driver Output Current	230mA
Power Factor	> 0.9
Electrical Classification	Class II
Surge Protection	Overload / Short Circuit

- · J · · · · · · ·	
OTHERS	
Adjustable Angle	Not Applicable
Body Material	Aluminium
Diffuser Material	PMMA
Rebate Scheme Approvals	Not Applicable
HACCP Approval	No
Weight	0.2 kg
Dimensions	Ø115 x 65 mm