


PURO

PURO12W250R

SAP CODE: 2001985




12W Indoor Tritone LED Oyster

The PURO series is a range of LED oysters featuring selectable colour temperature, smooth light distribution and flicker free technology, this light is perfect for numerous indoor residential applications.



Photometric
Diagram



Unit: cd
 C0/180 121.7deg
 C90/270 121.4deg

KEY INFORMATION

Lumen Output	960 / 1140 / 1080lm
Input Power	12W
Hole Cutout Size	N/A
Install	SURFACE MOUNT
Dimming Options	Non-Dimmable
Fitting Colour	WHITE
Warranty	5yr
IP Rating	IP20
IK Rating	N/A
IC Rating	N/A
Rebate Scheme Approvals	Pending Approval

PHOTOMETRIC

Efficacy	80 / 95 / 90lm/W
LED	SMD
CCT	3000 / 4000 / 5000K
CRI	>80
Beam Angle	120°

ELECTRICAL

Driver	Integral
Supply Input	220-240V, 50/60Hz
Driver Output Voltage	52V DC
Power Factor	>0.9
LED Input Current (nominal)	230mA
Useful life @Ta25° (L70)	50,000hr

CONSTRUCTION

Housing	Steel
Optics	Polycarbonate Diffuser
Adjustable Angle	N/A
Fixings/Hardware	Mounting Screws
Connection Type	Terminal Block
Total Weight	0.31kg
Dimensions	Ø250 x 79mm
Operating Ambient Temp.	-20 to 45°C
Electrical Classification	Class 1